

Work Positioners

Non-Straddle Work Positioners



Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
WP Series - Non-Straddle - 24" Load Center							
WP36-20	2000 lbs	36"	3-1/4"	60"x28"x65"	14" / 26 1/2"	3" / 8"	710 lbs
WP48-20	2000 lbs	48"	3-1/4"	72"x28"x65"	14" / 26 1/2"	3" / 8"	770 lbs
WP60-20	2000 lbs	60"	3-1/4"	84"x28"x65"	14" / 26 1/2"	3" / 8"	820 lbs
WP36-30	3000 lbs	36"	3-1/4"	60"x28"x65"	14" / 26 1/2"	3" / 8"	760 lbs
WP48-30	3000 lbs	48"	3-1/4"	72"x28"x65"	14" / 26 1/2"	3" / 8"	800 lbs
WP60-30	3000 lbs	60"	3-1/4"	84"x28"x65"	14" / 26 1/2"	3" / 8"	850 lbs

Not designed to lift wood pallets with bottom cross slats

Features

- 2000 - 3000 lb. capacity
- 24" load centers
- Lifting heights - 36" through 60"
- Fixed mast
- 2" thick x 6-1/4" wide x 42" long fixed steel forks
- 17" high fork carriage
- 14" fork I.D. & 26-1/2" fork O.D.
- 3-1/4" lowered height
- Steering wheel for greater mobility
- Lifting speed 2" per second 3000 lb. lift
- Fixed base
- Heavy-duty 12 volt deep cycle battery
- Custom micro processor charger
- Hand operated floor lock
- Nylon front load wheels
- Polyurethane rear wheels
- Optional slip-on platforms available

Straddle Work Positioners

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Base Legs I.D./O.D.	Wheel Dia. Front/Rear	Shipping Weight
WPS42 Series - 42" I.D. - 24" Load Center							
WPS4236-20	2000 lbs	36"	2"	59"x48"x65"	42" / 48"	5" / 8"	720 lbs
WPS4248-20	2000 lbs	48"	2"	71"x48"x65"	42" / 48"	5" / 8"	745 lbs
WPS4260-20	2000 lbs	60"	2"	83"x48"x65"	42" / 48"	5" / 8"	770 lbs
WPS4236-30	3000 lbs	36"	2"	59"x48"x65"	42" / 48"	5" / 8"	750 lbs
WPS4248-30	3000 lbs	48"	2"	71"x48"x65"	42" / 48"	5" / 8"	775 lbs
WPS4260-30	3000 lbs	60"	2"	83"x48"x65"	42" / 48"	5" / 8"	800 lbs
WPS50 Series - 50" I.D. - 24" Load Center							
WPS5036-20	2000 lbs	36"	2"	59"x56"x65"	50" / 56"	5" / 8"	730 lbs
WPS5048-20	2000 lbs	48"	2"	71"x56"x65"	50" / 56"	5" / 8"	755 lbs
WPS5060-20	2000 lbs	60"	2"	83"x56"x65"	50" / 56"	5" / 8"	780 lbs
WPS5036-30	3000 lbs	36"	2"	59"x56"x65"	50" / 56"	5" / 8"	760 lbs
WPS5048-30	3000 lbs	48"	2"	71"x56"x65"	50" / 56"	5" / 8"	785 lbs
WPS5060-30	3000 lbs	60"	2"	83"x56"x65"	50" / 56"	5" / 8"	810 lbs

For use in lifting wood pallets with bottom cross slats

Features

- 2000 - 3000 lb. capacity
- 24" load centers
- Lifting heights - 36" through 60"
- Fixed mast
- 2" thick x 6-1/4" wide x 42" long fixed steel forks
- 17" high fork carriage
- 14" fork I.D. & 26-1/2" fork O.D.
- 2" lowered height
- Steering wheel for greater mobility
- Lifting speed 4" per second 2000 lb. lift
- Lifting speed 2" per second 3000 lb. lift
- Fixed base
- Heavy-duty 12 volt deep cycle battery
- Custom micro processor charger
- Hand operated floor lock
- Phenolic front load wheels
- Polyurethane rear wheels
- Optional slip-on platforms available



Go Presto